KFR-05GW

Cooling Capacity	5000 Btu/h
Power supply	1Ph, 220-240V~ , 50Hz
Input	350 Watt
Rated current	1,6 Ampere
EER	3.01 W/W
Max. input consumption	520 Watt
Max. current	1.74 Ampere
Starting current	8.6 Ampere
Liquid side/ Gas side	1/4" / 3/8"
Refrigerant type	R22/300g
Indoor unit Dimension(W*D*H)	710x189x250mm
Indoor unit Net/Gross weight	7 / 8.5kg
Outdoor unit Dimension(W*D*H)	685x260x430mm
Outdoor unit Net/Gross weight	18.5 / 21kg
Application area	7-12 M2

KFR-09GW

Cooling Capacity	9000 Btu/h
Power supply	1Ph, 220-240V~ , 50Hz
Input	720 Watt
Rated current	3,7 Ampere
EER	2.41 W/W
Max. input consumption	1250 Watt
Max. current	5.5 Ampere
Starting current	16.3 Ampere
Liquid side/ Gas side	1/4" / 3/8"
Refrigerant type	R22/360g
Indoor unit Dimension(W*D*H)	710x189x250mm
Indoor unit Net/Gross weight	7.5/9kg
Outdoor unit Dimension(W*D*H)	685x260x430mm
Outdoor unit Net/Gross weight	21 / 23kg
Application area	10-17 M2

Contact us :

PT. Celest Mondy
Jl. Brigjen Katamso
Komplek Pluto Blok III No. 11
Tanjung Uncang - Batam 29432
Kepulauan Riau, Indonesia
Office : +62 778 736 8127
Fax : +62 778 736 8129
Website : http://www.mondygroup.com

Solusi pendingin
ruangan anda

Harga mulai dari
Rp. 1.950.000

www.mondygroup.com

MONDY **PT. CELEST MONDY**
Supply & Distribution of General/Electronic

12 & 18 BTU

KFR-12GW

Cooling Capacity	12000 Btu/h
Power supply	1Ph, 220-240V~ , 50Hz
Input	1200 Watt
Rated current	5.0 Ampere
EER	2.61 W/W
Max. input consumption	1500 Watt
Max. current	8.0 Ampere
Starting current	--- Ampere
Liquid side/ Gas side	1/4" / 1/2"
Refrigerant type	R22/560g
Indoor unit Dimension(W*D*H)	790x190x275mm
Indoor unit Net/Gross weight	9 / 11kg
Outdoor unit Dimension(W*D*H)	700x235x535mm
Outdoor unit Net/Gross weight	25 / 27kg
Application area	16-26 M2

KFR-18GW

Cooling Capacity	18000 Btu/h
Power supply	1Ph, 220-240V~ , 50Hz
Input	1700 Watt
Rated current	7.5 Ampere
EER	2.41 W/W
Max. input consumption	2200 Watt
Max. current	10.0 Ampere
Starting current	45.6 Ampere
Liquid side/ Gas side	1/4" / 1/2"
Refrigerant type	R22/900g
Indoor unit Dimension(W*D*H)	940x198x275mm
Indoor unit Net/Gross weight	10/13.5kg
Outdoor unit Dimension(W*D*H)	780x250x540
Outdoor unit Net/Gross weight	33 / 36kg
Application area	25-42 M2

48 BTU Floor Standing

YCF-48CR

Cooling Capacity	48000 Btu/h
Power supply	3Ph, 380-420V~ , 50Hz
Cooling Input	5000 Watt
Compressor Capacity	50838 Btu/h
Compressor Input	4520 Watt
Compressor Rated current(RLA)	7.50 Ampere
Compressor Locked rotor Amp(LRA)	≤55 Ampere
Rated current	9.0 Ampere
EER	2.41 W/W
Max. input consumption	6500 Watt
Max. current	12.5 Ampere
Starting current	55 Ampere
Liquid side/ Gas side	1/2" / 3/4"
Refrigerant type	R22/1950g
Indoor unit Dimension(W*D*H)	540x379x1775mm
Indoor unit Net/Gross weight	56 / 60kg
Outdoor unit Dimension(W*D*H)	990x355x965mm
Outdoor unit Net/Gross weight	90 / 94kg
Application area	60-100 M2

48 BTU Cassette

YCC-48CR (Indoor Unit)

Cooling Capacity	48000 Btu/h
Power supply	3Ph, 380V~ , 50Hz
Input	4600 Watt
Rated current	8.3 Ampere
Liquid side/ Gas side	12.7 / 19mm
Refrigerant type	R22
Indoor unit Dimension(W*D*H)	840×300×840 Body(mm)
	950×950×55 Panel(mm)
Indoor unit Net/Gross weight	35/42 Body(kg)
Application area	56-93 M2

YCC-48CR (outdoor unit)

Cooling Capacity	48000 Btu/h
Power supply	3Ph, 380V~ , 50Hz
Input	4650 Watt
Rated current	8,3 Ampere
Compressor Capacity	51000Btu/h
Compressor Input	4590W
Compressor Rated current(RLA)	9.6Ampere
Compressor Locked rotor Amp(LRA)	58 Ampere
Liquid side/ Gas side	1/2" / 3/4"
Refrigerant type	R22/2650g
Outdoor unit Dimension(W*D*H)	740×740×852mm
Outdoor unit Net/Gross weight	76 / 82kg